

Recirculating Air Pavement Cleaner



4.35 yd³ High Dump
109" WB Gas Cabover

Victory Sweepers 105 Green Cove Rd Huntsville, AL 35803 a division of ROOTS MULTICLEAN, Inc.

in-cab operating controls

LED lighting w/ integral strobes hydraulic dump & cleanout doors exclusive 'HOODS UP' feature stainless steel debris hopper

844-479-3373



LIBERTY GX SPECIFICATIONS

DEDDIO LIODDED	
DEBRIS HOPPER	405 1: 1/000 1: 1
	4.35 cubic yards/ 3.32 cubic meters
	Stainless Steel
	Vinyl Wrap
	Stainless Steel
	10"
	Replaceable, Polyethylene
	Stainless Steel
	1 on each side
, , ,	13.7" x 26"
	Hydraulic
	2 @ 4" x 16"
, ,	70"
	Electric In-cab
Separator Screen Constru	ıction 2 pc Stainless Steel
Separator Screen Mainter	nance Hydraulic assist access door
AUXILIARY ENGINE	
	4 Cycle / Gas
	Kohler
Model	ECH980
Number of Cylinders	2
	999 cc
	90 mm
	78.5 mm
	2 pc / Dry type w/ safety element
	Oil Pressure
IMPELLER	
	28"
	. 10 blade backward inclined high pressure
Maximum Coasd	2800 RPM
	4 Groove banded belt
	sion resisting grades of keyed welded steel
	2 Sealed & relubable ball bearings
nousing Construction	Welded steel
	Unobstructed for open airflow
	Replaceable corded rubber Coated for increased abrasion resistance
HYDRAULIC SYSTEM Pump Type	Fixed displacement gear
	Direct
	6 micron
,	
Back-up (optional)	13 gallons
Dack-up (optional)	40 # 50

	Electric in-cal
Diameter	39
Drive	Direct - Hydraulic moto
Tilt	Electric in-ca
Suspension	Sprin
	Vertical digge
	Oil tempered steel win
SWEEPING HOOD	Diant Continu / Dialetta La
	Blast - Suction / Right to Lei
	2 Trailing arm
	4 Spring
	Rubber stop
,,	2 piece
Material	Welded stee
	10" Diameter AR stee
Suction Tube	10" Diameter AR stee
Hood Widths	Standard 82", Optional 90
Flaps	3 Tota
	1/4" x 6.5" non-corded rubbe
Middle	3/8" x 6" non-corded rubbe
	1/2"x 6" non-corded rubbe
	Single rov
	Steel with virgin Tungsten Carbid
"LOODS LID" (Anti plani	ng)Independent hydraulic
	Electri In-cai
	Individually resettable
	Rocke
Monitoring Gauges	Hour mete
STANDARD CHASSIS	
	Isuzu/GM0
Model	NPR HD Gas / W4500 Ga
Capacity / GVWR	14,500 lb
PROPULSION ENGINE	
	4 Cycle / Ga
Model	+ Oyule / Oa
	CMDT LOG (Con IV) V/0 V/orto
Culindora	
Displacement	
Displacement Horsepower	
Displacement Horsepower Starter	
Displacement Horsepower Starter Alternator	
Displacement	.6.0 L / 365 cin
Displacement	6.0 L / 365 ci 297 hp @ 4,300 rpr 112 145 am 12v - 750 CC. Spin-o.
Displacement	6.0 L / 365 cit 297 hp @ 4,300 rpn 112 145 amp 12v - 750 CC. Spin-or
Displacement	6.0 L / 365 ci 297 hp @ 4,300 rpn 12 145 am 12v - 750 CC/ Spin-oi Dry-type
Displacement	6.0 L / 365 ci 297 hp @ 4,300 rpn 12 145 am 12v - 750 CC/ Spin-oi Dry-type
Displacement	GMPT L96 (Gen IV) V8 Vortee 6.0 L / 365 c. 297 hp @ 4,300 rpn 120 145 am 12v - 750 CC/ Spin-or Dry-type 6L90 6-speed double overdrive Automatic

	_					
ш	ᄓ	$\sim \Lambda$	רווא	1M/H	IEEL	·Q

Configuration	2 Front, 4 Rear
	Tubeless / Steel belted radials
Tire Size	225/70R19.5F/G
Wheels	Steel disc / one piece

BRAKE

Type	Front disc / Rear drun
Power	Vacuum/Hydraulic with 4-channel ABS
Parking	Mechanical / Trans mounted

CA

Туре	Cab over Engine
Engine Access	Manual tilt
Construction	Steel
Air Conditioning	Standard
Radio	Standard
Windows	Electric
Door Locks	Electric
Steering	Integral Power

WEIGHTS AND DIMENSIONS

Total Empty Weight	9,500 lbs
Chassis Only Curb Weight	4,950 lbs
Wheel Base	109'
Turning Diameter	33' 6'
Overall Length	214'
Overall Height	92'
Overall Width	92'
Sweeping Width (hood only)	82" or 90'
Sweeping Width (hood and left broom)	101'
Sweeping Width (hood and dual brooms)	116'

OPTIONAL FOLIPMENT

OF HOMAL EQUIT WENT	
Engine Shroud	LED Hood Lights
Spray Bar	Spare Tire & Wheel
LED Bar Light	12 Volt Backup
Dump Assist Shaker	Tool Boxes
Package Travs	Tool Box Travs

Back-up Alarm Hand Hose 6" Big Bumper Hopper Drain

STANDARD 12 MONTH LIMITED WARRANTY

12 Month, 1200 Hour Warranty

(whichever occurs first)

- 1. Chassis Limited 36 months or 36,000 miles
- 2. Kohler Auxiliary Engine Limited 12 mo or 1200 hrs
- 3. Sweeper Unit Limited 12 months or 1200 hrs
- 4. Hydraulics Limited 12 months or 1200 hrs
- 5. Electrical Controls & Components Limited 12 mo or 1200 hrs
- 6. LED Lighting Limited 12 mo or 1200 hrs
- 7. Carbide Skid Shoes Limited 12 mo or 1200 hrs

Model shown with optional equipment . Specifications subject to change without notice

8. Impeller Fan - Limited 12 mo or 1200 hrs



. 105 gallons

... Polyethylene

... 12 volt, Diaphram

Purpose Powers all hydraulic functions without auxiliary engine


Controls..

DUST SUPPRESSION
Water Capacity.....


Tank Construction.

Pump Type .





. 6 Forward, 1 Reverse



www.victorysweepers.com

844-479-3373

Victory Sweepers, a division of ROOTS MULTICLEAN, Inc. 105 Green Cove Rd, Huntsville, AL 35803

^{*} Please read actual warranty for details and limitations *Combination of options may require heavier GVW chassis