www.victorysweepers.com



VICTORY CX

- 24.9 hp gas auxiliary engine
- 20 inch dia Hardox steel fan
- 50 gallon water tank
- 26 inch dia gutter broom
- over-sized tool storage boxes
- reverse sweep pickup head
- in-cab operating controls



CX mounted on Ford F250

Recirculating Air Pavement Cleaner



2.7 yd³ High Dump Stainless Steel Hopper 3/4 Ton Conventional Chassis Low Clearance

CX mounted on Chevrolet 2500



VICTORY CX SPECIFICATIONS

DEBRIS HOPPER	
Capacity	2.7 cubic yards/ 2.06 cubic meters
	Stainless Steel
	Vinyl Wrap
	Stainless Steel
	10"
Suction Tube Material	Replaceable, Polyethylene
	2,(1 on each side)
	9.75" x 20"
	Hydraulic
	2 @ 3" x 10"
	65"
	Electric In-cab
Separator Screen Construction	Stainless Steel
Separator Screen Maintenance	eHydraulic access door
AUXILIARY ENGINE	
	4 Cycle / Gas
	iGX800 Air Cooled
	2 V-Twin
	779 cc
	3.23 in/82 mm
	2.83 in/72 mm
	24.9 BHP/18.6 KW
	Spin on
	2 pc / Dry type w/ safety element
Fuel	Gasoline - Electronic Fuel Injection
	•
IMPELLER	
Type 8 k	blade backward inclined high pressure
Drive	Multi-groove banded belt
Construction2 Abrasion r	resisting grades of keyed welded steel
Mounting	2 Sealed & relubable ball bearings
	Welded steel
Housing Type	Unobstructed for open airflow
Liner	Replaceable corded rubber
Liner BoltsCoa	ated for increased abrasion resistance
HYDRAULIC SYSTEM	
	Fixed displacement gear
	Belt
Pumn Canacity	5 GPM
	10 micron
	10 micron
Hydraulic Back-up System (opt	
	12 volt DC
	In cab
Purpose Powers all hydra	aulic functions without auxiliary engine
DUST SUPPRESSION	
	50 gallons
	Aluminum

Pump Type ..

CURB BROOM	
Controls	Electric in-cab
Diameter	
Drive	Direct - Hydraulic motor
Tilt	In-cab Electric
Suspension	
Bristle Type	
Bristle Material	
Bristle Length	
SWEEPING HOOD	
Туре	
Towing Type	
Suspension	
Up Storage	
Туре	
Material	
Pressure Tube	10" Diameter AR steel
Suction Tube	
Hood Width	82"
Direction	
Skids	Single row
Skid Material	. Steel with virgin Tungsten Carbide
CONTROLS	
Туре	Flectric
Location	
Circuit Breakers	
Switches	
Monitoring	
WOIIIOIIII9	Поиг meter
STANDARD CHASSIS	
Make	Ford
Model	F-250
Capacity / GVWR	10,000 lbs
Wheelbase	142"
PROPULSION ENGINE	
Type/Fuel	4 Cycle / Gas
Cylinders	
Displacement	6.2 L EFI
Horsepower/Torque	
Starter	
Alternator	
Oil Filter	
Air Filter	
All 1 litter	Dry-type
TRANSMISSION	
Type	
Speeds	6 Forward, 1 Reverse
ADDITIONAL CHASSIS OPTIONS	
Make /Model	
Make /Model	
Make /Model	Isuzu / NPR
Maka /Madal	others upon engroval

others upon approval

Total Empty Weight... Chassis Only Curb Weight ... Wheel Base Turning Radius .. Overall Length .. Overall Height. Overall Width... Sweeping Width (hood only). Sweeping Width (hood and left broom) ... LED Hood Lights Back-up Alarm Spray Bar Spare Tire & Wheel LED Bar Light 12 Volt Backup Dump Assist Shaker Tool Boxes STANDARD 12 MONTH LIMITED WARRANTY 12 Month, 1200 Hour Warranty (whichever occurs first) 1. Chassis - Limited 36 months or 36,000 miles 2. Honda Auxiliary Engine - Limited 36 months 3. Sweeper Unit - Limited 12 months or 1200 hrs 4. Impeller Fan - Limited 60 mo or 5000 hrs * Please read actual warranty for details and limitations * Combination of options may require heavier GVW chassis * Model shown with optional equipment * Specifications subject to change without notice

24'6"

223

. 82"

. 82"

Hand Hose 5"

Big Bumper

Hopper Drain





..... 12 volt, Diaphram

www.victorysweepers.com

ADDING VALUE

844-479-3373