

Recirculating Air Pavement Cleaner

- Isuzu NPR gas chassis 109 WB
- 24.9 hp gas auxiliary engine
- 20 inch dia Hardox steel fan
- 50 gallon water tank
- 39 inch dia gutter broom
- in-cab remote broom tilt
- over-sized tool storage boxes
- reverse sweep pickup head
- in-cab operating controls
- exclusive 'HOODS UP' feature



Victory Sweepers 631 Fields Road Laceys Spring, AL 35754 A division of ROOTS MULTI CLEAN, Inc.

844-479-3373



VICTORY CXI SPECIFICATIONS

DEBRIS HOPPER	
	2.7 cubic yards/ 2.06 cubic meters
	Stainless Steel
Exterior Finish	Vinyl Wrap
Interior Finish	Stainless Steel
Suction Tube Diameter	10"
Suction Tube Material	Replaceable, Polyethylene
Inspection Doors	2,(1 on each side)
Inspection Door Opening	9.75" x 20"
	Hydraulic
Dump Cylinders	2 @ 3" x 20"
Dump Height	70"
	Electric In-cab
Separator Screen Construction	Stainless Steel
	Hydraulic access door
AUXILIARY ENGINE	
	4 Cycle / Gas EFI
Make	Honda
Model	iGX800 Air Cooled
Number of Cylinders	2 V-Twin
Displacement	779 cc
Bore	3.23 in/82 mm
Stroke	2.83 in/72 mm
Brake Horsepower	24.9 BHP/18.6 KW
Oil Filter	Spin on
Air Filter	2 pc / Dry type w/ safety element
Fuel	Gasoline - Electronic Fuel Injection
IMPELLER Discount of the second of the secon	20"
Diameter	20"
	lade backward inclined high pressure
	Multi-groove banded belt
	esisting grades of keyed welded steel
	2 Sealed & relubable ball bearings
	Welded steel
	Unobstructed for open airflow
	Replaceable corded rubber
Liner BoltsCoa	ted for increased abrasion resistance
HYDRAULIC SYSTEM	F'
	Fixed displacement gear
	Belt
	5 GPM
	10 micron
Reservoir Capacity	10 gallons
Hydraulic Back-up System (opti	onal)
	12 volt DC
	In cab
Purpose Powers all hydra	ulic functions without auxiliary engine
DUST SUPPRESSION	
Water Capacity	50 gallons

CURB BROOM	
	Electric in-cab
	39"
	Direct - Hydraulic motor
	Electric in-cab
	Spring
	Vertical digger
	Oil tempered steel wire
Bristle Length	26"
SWEEPING HOOD	
Type	Blast - Suction / Right to Left
	2 Trailing arms
	4 Springs
	Rubber stops
	2 piece
	10" Diameter AR steel
	Standard 82", Optional 90"
	3 Total
	Forward and reverse
	Single row
Skid Material	. Steel with virgin Tungsten Carbide
"HOODS UP" (Anti-plowing)	Independent hydraulics
"HOODS UP" Controls	Electric in-cab
CONTROLS	
	Flectric
Туре	Electric
TypeLocation	In-cab
TypeLocationCircuit Breakers	In-cab Individually resettable
Type	In-cab Individually resettable Rocker
Type	In-cab Individually resettable
Type Location Circuit Breakers Switches Monitoring	In-cab Individually resettable Rocker
Type	In-cab Individually resettable Rocker Hour meter
Type	In-cab Individually resettable Rocker Hour meter
Type	In-cabIndividually resettable RockerHour meterIsuzu
Type	In-cab Individually resettable Rocker Hour meter
Type	In-cabIndividually resettable RockerHour meterIsuzu
Type	In-cab Individually resettable Rocker Hour meter Isuzu NPR Gas 12,000 lbs
Type	In-cab Individually resettable Rocker Hour meter Isuzu NPR Gas 12,000 lbs
Type	In-cab Individually resettable Rocker Hour meter Isuzu NPR Gas 12,000 lbs 4 Cycle / Gas
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders Displacement	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders Displacement Horsepower Switches Sw	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders Displacement Horsepower Torque.	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders Displacement Horsepower Torque Starter	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders Displacement Horsepower Torque Starter Alternator	
Type	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders Displacement Horsepower Torque Starter Alternator Battery Oil Filter	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders Displacement Horsepower Torque Starter Alternator Battery Oil Filter	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders Displacement Horsepower Torque Starter Alternator Battery Oil Filter	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders Displacement Horsepower Torque Starter Alternator Battery Oil Filter Air Filter TRANSMISSION	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders Displacement Horsepower Torque Starter Alternator Battery Oil Filter Air Filter TRANSMISSION Make	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders Displacement Horsepower Torque Starter Alternator Battery Oil Filter Air Filter TRANSMISSION Make	
Type Location Circuit Breakers Switches Monitoring STANDARD CHASSIS Make Model Capacity / GVWR PROPULSION ENGINE Type/Fuel Model Cylinders Displacement Horsepower Torque Starter Alternator Battery Oil Filter Air Filter TRANSMISSION Make Type	

TIRES AND WHEELS 2 Front, 4 Rear Configuration 2 Front, 4 Rear Tire Type Tubeless / Steel belted radials Tire Size 215/85R16E Wheels Steel disc / one piece
BRAKES TypeFront disc / Rear drum PowerVacuum/Hydraulic with 4-channel ABS ParkingMechanical / Trans mounted
CAB Cab over Engine Type
WEIGHTS AND DIMENSIONS Total Empty Weight 9,200 lbs Chassis Only Curb Weight 5,204 lbs Wheel Base 109" Turning Diameter (curb to curb) 31' 5" Overall Length 214" Overall Height 92" Sweeping Width 92" or 90" Sweeping Width (hood and left broom) 101" Sweeping Width (hood and dual brooms) 116"

STANDARD 12 MONTH LIMITED WARRANTY

12 Month, 1200 Hour Warranty

(whichever occurs first)

LED Hood Lights

Dump Assist Shaker

Spray Bar

LED Bar Light

- 1. Chassis Limited 36 months or 36,000 miles
- 2. Honda Auxiliary Engine Limited 36 months
- 3. Sweeper Unit Limited 12 months or 1200 hrs
- 4. Impeller Fan Limited 60 mo or 5000 hrs

* Please read actual warranty for details and limitations 'Combination of options may require heavier GVW chassis 'Model shown with optional equipment 'Specifications subject to change without notice

Illuminator Bumper

Spare Tire & Wheel

. 12 Volt Backup

Tool Boxes

Back-up Alarm

Hand Hose 5"

Big Bumper

Hopper Drain



.....Aluminum 12 volt, Diaphram

Tank Construction

Pump Type .







www.victorysweepers.com

844-479-3373

Victory Sweepers, A division of ROOTS MULTI CLEAN, Inc. 631 Fields Road, Laceys Spring, AL 35754