



Recirculating Air Street Sweeper

6.58 yd³ Low Dump Stainless Steel Hopper Isuzu NRR Diesel Chassis 19,500 lbs GVWR 132" Wheelbase



Victory Sweepers 631 Fields Road Laceys Spring, AL 35754

844-479-3373



VICTORY MARK 6 SPECIFICATIONS

DEBRIS HOPPER	
Capacity	6.58 cubic yards/ 5.03 cubic meters
Construction	Stainless Steel
Exterior Finish	Vinyl Wrap or Stainless Steel
Interior Finish	Uncoated Stainless Steel
Suction Tube Diameter	12" with quick disconnect
Suction Tube Material	Abrassion Resistent Steel
	Electric
	1 on each side
	13.7" x 26"
	Hydraulic low dump to rear
	2 @ 4" x 16"
	32"
	Electric In-cab
	on Stainless Steel
	ce Hydraulic assist access door
Hopper Drain System	Provided on rear door
ALIVILIA DV ENOINE	
AUXILIARY ENGINE	4 Cuala / Tumba Affaranal Di
	4 Cycle / Turbo Aftercooled Diesel
	Kubota
	V3307-CR-TI-E4B
	4
	203 cu in/3.33 litres
	3.70 in/94 mm
Stroke	4.72 in/120 mm
Brake Horsepower	74.3 HP/55.4 KW
Oil Filter	Spin on
Air Filter	2 pc / Dry type w/ safety element
	Vater temp, water level and oil pressure
	Stainless Steel
2.19.110 01110001111111111111111111111111	Camboo Coo.
IMPELLER	
	blade backward inclined high pressure
	3V 8-Groove banded belt
Construction 2 Abrasian	resisting grades of keyed welded steel
Maurina	2 Cooled 8 roll bobbs boll begrings
	2 Sealed & relubable ball bearings
	Welded steel
	Unobstructed for open airflow
	Replaceable corded rubber
Liner BoltsCo	oated for increased abrasion resistance
HYDRAULIC SYSTEM	
	Fixed displacement gear
	Direct
	Tandem 5/5 GPM
System Filtration	10 micron
Reservoir Capacity	18 gallons
	•
Hydraulic Back-up System	
Pump Type	12 volt DC
	In cab
	raulic functions without auxiliary engine
i aiposo i oweis ail liyu	radio ranonono minout auxiliary engine
DUST SUPPRESSION	
	105 gallons
	Polyethylene
	12 volt, Diaphram
Cantrolo	12 voil, Diapriram

CURB BE Type Controls Diameter. Drive Tilt Suspension Bristle Typ Bristle Ma Center Br
SWEEPIN Type Towing Ty Suspensia Up Storag Material Pressure Suction Ti Hoses Hood Wid Flaps Skid Mate Direction "HOODS" "HOODS "HOOD F
CONTRO Type Location Circuit Bre Switches. Monitoring
STANDAR Make Model Capacity
PROPUL Type/Fuel Model Cylinders. Displacen Horsepow Torque Starter Alternator Battery

	Right and Left Vertical S
	Electric in
	Direct - Hydraulic m
	Hydraulic in
	Sr
	Vertical di
	Oil tempered steel wire -
Center Broom Deflector	Ru
SWEEPING HOOD	
	Regenerative / Blast Or
Towing Type	2 AdjustableTrailing a
	4 Spr
Up Storage	Rubber s
Material	Welded s
Pressure Tube	12" Diameter AR s
	12" Diameter AR s
Hoses 12" diame	ter molded rubber w/ quick discon-
Hood Width	
Flaps	5 1
Skids	Double
Skid Material	Steel with virgin Tungsten Can
Direction	Forward and reve
"HOODS UP" (Anti-plowing)	Independent hydrau
	Electric in
	Right
CONTROLS	
Type	Ele
Location	In-
Circuit Breakers	Individually resett
Switches	Ro
	ach, Oil Pressure, Coolant Temp, \
STANDARD CHASSIS	
Make	Is
Model	
Capacity / GVWR	
PROPULSION ENGINE	
	4 Cycle / Di
Model	Isuzu 4HK1-TC turbo interco
	5.2 L / 31
DISDIACEMENT	
Horsepower	215 hp @ 2,500
Horsepower Torque	215 hp @ 2,500 452 lb-ft @ 1,850

	NRR 19,500 lbs
	,,,,,
PROPULSION ENGINE	
	4 Cycle / Diesel
Model	Isuzu 4HK1-TC turbo intercooled
Cylinders	4
Displacement	5.2 L / 317 cid
Horsepower	215 hp @ 2,500 rpm
Torque	452 lb-ft @ 1,850 rpm
Starter	12v
Alternator	140 amp
Battery	dual - 750 CCA
Oil Filter	Spin-on
Air Filter	
Туре	Aisin A465id 6-speed double overdrive Automatic



Configuration	2 Front, 4 Rear
	Tubeless / Steel belted radials
	225/70R19.5G
Wheels	Steel disc / one piece

BRAKES

Type	Four-wheel disc
Power	Vacuum/Hydraulic with 4-channel ABS
Parking	Mechanical / Trans mounted

Туре	Cab over Engine
Engine Access	Manual til
Construction	Stee
Air Conditioning	Standard
Radio	Standard
Windows	Electric
Door Locks	Electric
Steering	

TypeTwo-Camera System with Color Mor	Type	Two-Camera	System with	Color Mon
--------------------------------------	------	------------	-------------	-----------

WEIGHTS AND DIMENSIONS

Total Empty Weight	13,500 lbs
Chassis Only Curb Weight	
Wheel Base	132
Turning Diameter (curb to curb)	40' 0
Overall Length	245
Overall Height	102
Overall Width	92
Sweeping Width (hood only)	80
Sweeping Width (hood and single broom)	104
Sweeping Width (hood and dual brooms)	130

OPTIONAL EQUIPMENT

8" Diameter Auxiliary Suction Hose (spring boom) 8" Diameter Auxiliary Suction Hose (power boom)

High Pressure Washdown LED Bar Light Gutter Broom Scrub Illuminator Bumper Extra 95 gal Water Tank

Hopper Deluge **Dual Steering**

STANDARD 12 MONTH LIMITED WARRANTY

12 Month, 1200 Hour Warranty (whichever occurs first)

- 1. Chassis Limited 36 months or 36,000 miles
- 2. Kubota Auxiliary Engine Limited 24 mo or 2000 hrs
- 3. Sweeper Unit Limited 12 months or 1200 hrs
- 4. Impeller Fan Limited 60 mo or 5000 hrs



Controls ..





www.victorysweepers.com

844-479-3373

Victory Sweepers, A division of ROOTS MULTI CLEAN, Inc. 631 Fields Road, Laceys Spring, AL 35754

^{*} Please read actual warranty for details and limitations *Combination of options may require heavier GVW chassis *Model shown with optional equipment

^{*}Specifications subject to change without notice