

www.victorysweepers.com

UNO LPG

LIQUID PROPANE GAS



4.35 cubic yard single engine hydraulically driven Recirculating Air Pavement Cleaner

The Victory UNO is a single engine hydraulically powered parking lot sweeper that derives its power from the truck engine via a belt driven hydraulic pump thereby eliminating the need for an auxiliary engine.

The UNO LPG allows the truck engine to operate on either regular gasoline or propane. When the vehicle is started and propane is available, it automatically switches to propane. Once depleted, the sweeper switches back to gasoline. Manual control is also provided in the cab.

The Victory UNO features a 4.35 cubic yard hopper available in either aluminum or 304 stainless steel, a 39-inch diameter gutter broom with in-cab tilt, 105-gallon dust control system, large optional aluminum rear tool storage, a 26-inch blower fan constructed with Hardox steel and full width sweeping head with our exclusive "HOODS UP" anti-plow feature.

The Victory UNO is available on both the 12,000 lbs GVWR Isuzu NPR (aluminum hopper) and the 14,500 lbs GVWR Isuzu NPR-HD.



VICTORY SWEEPERS UNO SPECIFICATIONS

DEBRIS HOPPER

Capacity	. 4.35 cubic yards/ 3.32 cubic meters
Construction	Aluminum, (Stainless Steel optional)
Exterior Finish	Vinyl Wrap
Interior Finish	Aluminum, (Stainless Steel optional)
Suction Tube Diameter	10 inch
Suction Tube Material	Replaceable, Polyethylene
Engine Shroud (optional)	Stainless Steel
Inspection Doors	1 on each side
Inspection Door Opening	13.7 inch x 26 inch
Dump Type	Hydraulic
Dump Height	
Dump Controls	Electric In-cab
Separator Screen Construction	2 pc Stainless Steel
Separator Screen Maintenance	Hydraulic assist access door

HYDRAULIC SYSTEM

Gauges	Heads up LCD display
Reservoir Capacity	36 Gallons
Main Pump	
Gallons Per Minute	8 gpm
Fan Motor	
Dump Cylinders	(2) 4 inch x 16 inch
Head Cylinders	
Broom Cylinder	2 inch x 4 inch
Hoods Up Cylinder	1.5 inch x 6.5 inch
Dump Door Cylinder	(2) 1.5 inch x 6.5 inch
Filter (HP)	Cartridge
Filter (LP)	Spin-on
ProtectionLow oil, high to	emperature, overspeed shutdown
Hydraulic Fluid Grade	AW 46
Fluid Gauge	Sight gauge with temperature
Cooling	DC forced air oil cooler
=	

IMPELLER

Diameter	26 inch
Туре	10 blade backward inclined high pressure
Drive	Mulit-groove banded belt
Construction	2 Abrasion resisting grades of keyed welded steel
Mounting	2 Sealed & relubable ball bearings
Housing Constru	ctionWelded steel
Housing Type	Unobstructed for open airflow
Liner	Replaceable corded rubber
Liner Bolts	Coated for increased abrasion resistance

DUST SUPPRESSION

Water Capacity	105 gallons
Tank Construction	Polyethylene
Pump Type	12 volt, Diaphran
Controls	In cal

CURB BROOM

Controls	Electric in-cab
Diameter	39 inches
Drive	Direct - Hydraulic motor
Tilt	Electric in-cab
Suspension	Spring
Bristle Type	Vertical digger
Bristle Material	Oil tempered steel wire
Bristle Length	26 inches

SWEEPING HOOD

SWLLFINGTIOOD	
Туре	Blast - Suction / Right to Left
Towing Type	2 Trailing arms
Suspension	4 Springs
Up Storage	Rubber stops
Туре	2 piece
	Welded steel
Pressure Tube	10 inch diameter AR steel
Suction Tube	10 inch diameter AR steel
Hood Widths	Standard 82 inches, Optional 90 inches
Flaps	3 Total
Skids	Single row reversible
Skid Material	Steel with virgin Tungsten Carbide
"HOODS UP"" (Anti-plow	ing)Independent hydraulics
"HOODS UP" Controls	Electric in-cab

CONTROLS

Туре	Electric
Location	In-cab
Circuit Breakers	Individually resettable
Switches	Rocker

STANDARD CHASSIS

Make	Isuzu
Model	NPR Gas
Capacity / GVWR	12,000 lbs

PROPULSION ENGINE

Type/Fuel	4 Cycle / Gas
Model	GMPT L8T (Gen V)
Cylinders	8
	6.6 L / 400 cid
	350 hp @ 4,500 rpm
Starter	12v
Alternator	170 amp
Battery	12v - 750 CCA
Oil Filter	Spin-on
Air Filter	

TRANSMISSION

Make	6L90 6-speed double overdrive
Type	Automatic
Speeds	

TIRES AND WHEELS

Configuration	2 Front, 4 Rear
	Tubeless / Steel belted radials
Tire Size	215/85R16E
Nheels	Steel disc / one piece

BRAKES

Type	Front disc / Rear drum
	. Vacuum/Hydraulic with 4-channel ABS
Parking	Mechanical / Trans mounted

CAB

Type	Cab over Engine
Engine Access	
Construction	Steei
Air Conditioning	Standard
Radio	
Windows	Electric
Door Locks	Electric w/remote
Steering	Integral Power

WEIGHTS AND DIMENSIONS

Chassis GVWR	12,000 lbs
Chassis Only Curb Weight	5,204 lbs
Wheel Base	109 inches
Turning Diameter	33 ft 6 inches
Overall Length	214 inches
Overall Height	92 inches
Overall Width	92 inches
Sweeping Width (hood only)	90 inches
Sweeping Width (hood and left broom)	101 inches
Sweeping Width (hood and dual brooms)	116 inches

OPTIONAL EQUIPMENT

· ·	
Hand Hose 6 inch dia	Hopper Drain
Spare Tire & Wheel	Hood Lights
12 Volt Backup	Big Bumper
Tool Box Shelves	Tool Boxes
Illuminator Bumper	Dump Shaker
	Hand Hose 6 inch dia Spare Tire & Wheel 12 Volt Backup Tool Box Shelves

STANDARD LIMITED WARRANTY


- 1. Chassis Limited 36 months or 36,000 miles*
- 2. Chassis Drivetrain Limited 60 months or 75,000 miles*
- 3. Sweeper Unit Limited 12 months or 1200 hours*


Model shown with optional equipment • Specifications subject to change without notice

4. Impeller Fan - Limited 60 months or 5000 hours*









www.victorysweepers.com

844-479-3373

Victory Sweepers, a division of ROOTS MULTICLEAN, Inc. 631 Fields Road, Laceys Spring, AL 35754

^{*} Whichever occurs first (read actual warranty for details and limitations) Combination of options may require heavier GVW chassis